

Anthem STR Power Amplifier

Eindversterkers



Technische specificaties

Merk	Anthem
Model	STR Power Amplifier
Productcategorie	Eindversterkers
Frequentiebereik	8Ω = 20 Hz - 20 kHz ± 0.1 dB 4Ω = 20 Hz - 20 kHz ± ?? dB 2Ω = 20 Hz - 20 kHz ± ?? dB
Ingangen	Single-Ended, Balanced, Relay Trigger (3.5-mm Mono Jack)
Uitgangen	Speaker Binding Posts, Relay Trigger (3.5-mm Mono Jack)
Kanalen	2
Ingangsgevoeligheid	2.1 Vrms
Ingangsimpedantie	10kΩ (RCA), 15kΩ (XLR)
Slew rate	30 V/μs
Kanaalscheiding	101 dB (100 Hz), 98 dB (10 kHz)
Overspraak	n/a

Technische specificaties

Signaal-ruisverhouding	121 dB (IEC-A, ref. 400 W)
Totale harmonische vervorming plus ruis	0.0007% (1 kHz), 0.004% (20 kHz) @ 400 W
Intermodulatievervorming	ITU-R (19 kHz + 20 kHz) 0.0006% @ 300 W SMPTE (60 Hz + 7 kHz) 0.0016% @ 300 W
Dempingsfactor	(20 Hz - 1 kHz) 360
Display voorzijde	7" Graphic Display (Power Meter, Status, en Navigation)
Constructie	Anodized Aluminum Faceplate with Aluminum Chasis
Afmetingen (D) (excluding Power Cord)	18-1/2" (47 cm)
Afmetingen (W)	17" (43.2 cm)
Afmetingen (H) (with feet)	6-3/4" (17.2 cm)
Hoogte met rackmontage	n/a
Verbruik zonder signaal	65 W
Uitvoering 120 V	In countries where the line voltage is 120 V, this product operates from a single phase AC power source that supplies between 108 V and 132 V at a frequency of 60 Hz.
Uitvoering 220-240 V	In countries where the line voltage is 220, 230, or 240 V, this product operates from a single phase AC power source that supplies between 198 V and 264 V at a frequency of 50 Hz.
Gewicht	60 lb (27.3 kg)