

Fyne Audio F1-12S

Luidsprekers



Technische specificaties

Merk	Fyne Audio
Model	F1-12S
Productcategorie	Luidsprekers
Systeemtype	2 way, downwards firing port, met BassTrax Tractrix diffuser
Nominale impedantie	8 Ohm
Luidsprekerbezetting	1 x 300mm IsoFlare point source driver with FyneFlute surround, multi-fibre bass / midrange cone, met 75mm titanium dome compression tweeter, neodymium magnet system
Afmetingen (H x B x D)	1350 x 450 x 680mm (53.2" x 17.7 x 28.6")
Aanbevolen versterkervermogen (W RMS)	20 - 350
Piekbelaastbaarheid (W)	600
Continue belaatbaarheid (W RMS)	175

Technische specificaties

Gevoeligheid (2,83 V / 1 m)	96dB
Frequentiebereik (-6 dB, in de ruimte)	24Hz - 26kHz
Scheidingsfrequentie	750Hz
Type wisselfilter	Bi-wired passive low loss, 2nd order low pass, 2nd order high pass, Deep Cryogenically Treated
Systeeminstellingen	High frequency energy (750Hz - 26kHz) +/-3dB Presence (2.5kHz - 5.0kHz) +/- 3dB
S-Trax-positie vanaf voorrand kast	133mm (5.2")
SuperTrax-positie vanaf voorrand kast	109mm (4.3")
Nettogewicht per stuk	72kg
Afwerkingen	Piano Gloss Walnoot