

Fyne Audio F501SP

Luidsprekers



Technische specificaties

Merk	Fyne Audio
Model	F501SP
Productcategorie	Luidsprekers
Systeemtype	2 ½ way, downwards firing port, met BassTrax™ Tractrix diffuser*, twin cavity loading system
Nominale impedantie	8 Ohm
Luidsprekerbezetting	1 x 150mm IsoFlare point source driver, multi-fibre bass / midrange cone, FyneFlute surround with 25mm magnesium dome compression tweeter, neodymium magnet system. 1 x 150mm multi-fibre bass cone, FyneFlute surround.
Afmetingen (H x B x D)	984 x 288 x 320mm (38.7 x 11.3 x 12.7")
Aanbevolen versterkervermogen (W RMS)	30 - 180
Continue belastbaarheid (W RMS)	80

Technische specificaties

Gevoeligheid (2,83 V / 1 m)	91dB
Frequentiebereik (-6 dB, in de ruimte)	36Hz - 34kHz
Scheidingsfrequentie	250Hz & 1.7kHz
Type wisselfilter	Bi-wired passive low loss, 2nd order low pass, 1st order high pass. Cryo-Lite treated.
S-Trax-positie vanaf voorrand kast	44mm (1.7")
SuperTrax-positie vanaf voorrand kast	20mm (0.8")
Nettogewicht per stuk	21.0kg (46.3lb)
Afwerkingen	Natural Walnoot / Piano Gloss Walnoot / Piano Gloss Zwart / Piano Gloss Wit