

Fyne Audio F702SP

Luidsprekers



Technische specificaties

Merk	Fyne Audio
Model	F702SP
Productcategorie	Luidsprekers
Systeemtype	2 ½ way, downwards firing port, met BassTrax™ Tractrix diffuser*, twin cavity loading system
Nominale impedantie	8 Ohm
Luidsprekerbezetting	1 x 200mm IsoFlare™ point source driver, multi-fibre bass / midrange cone, FyneFlute™ surround with 25mm magnesium dome compression tweeter, ferrite magnet system . 1 x 200mm multi-fibre bass / midrange cone, FyneFlute™ surround.
Afmetingen (H x B x D)	1126 x 439 x 443mm (44.3 x 17.3 x 17.4")
Aanbevolen versterkervermogen (W RMS)	30 - 200
Piekbelastbaarheid (W)	400

Technische specificaties

Continue belastbaarheid (W RMS)	100
Gevoeligheid (2,83 V / 1 m)	92dB
Frequentiebereik (-6 dB, in de ruimte)	28Hz - 34kHz
Scheidingsfrequentie	250Hz & 1.8kHz
Type wisselfilter	Bi-wired passive low loss, 2nd order low pass, 1st order high pass. Cryogenically treated
Kastconstructie	Pressed high density birch ply with extensive internal bracing
S-Trax-positie vanaf voorrand kast	63mm (2.5")
SuperTrax-positie vanaf voorrand kast	39mm (1.5")
Nettogewicht per stuk	37.5kg (82.7lbs)
Afwerkingen	Natural Walnoot / Piano Gloss Walnoot / Piano Gloss Zwart / Piano Gloss Wit