

MartinLogan Monument 7XW

Inbouwluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Monument 7XW
Productcategorie	Inbouwluidsprekers
Frequentiebereik	52-25,000 Hz $\pm$ 3 dB
Impedantie	4 Ω . Compatible with 4, 6, or 8 ohm rated amps.
Gevoeligheid	95 dB @ 2.83 volts/ meter
Luidsprekerbezetting	Custom air core coil inductors, polypropylene film capacitors, en low DF electrolytic capacitors. Thermal/current protection.
Afstraling tweeter (horizontaal x verticaal)	80° x 30°
Scheidingsfrequentie	200, 3200 Hz
Hogetonenunit	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.

Technische specificaties

Middentonenunits	6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Lagetonenunit	Twee 6.5-inch (16.5 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Passieve radiatoren	Drie 6.5-inch (16.5 cm) unidirectional black carbon fiber cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Aanbevolen versterkervermogen	20-300 W
Maximale belastbaarheid	150 W
Luidsprekerterminals	Push style (two sets for easy installation)
Afmetingen (overall size)	46.86 x 10.6 x 4.11 inch (1190.2 x 269.2 x 104.3 mm)
Benodigde wandopening inclusief tolerantie	45.57 x 9.29 inch (1157 x 236 mm)
Uitsteek vanaf wand	0.31 inch (7.8 mm)
Diepte achter wand	3.8 inch (96.5 mm)
Gewicht	44.5 lb (20.2 kg)