

MartinLogan Motion 4i

Monitorluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion 4i
Productcategorie	Monitorluidsprekers
Frequentiebereik	70-23,000 Hz $\pm$ 3dB
Impedantie	4 Ω Compatible with 4, 6, or 8 Ohm rated amplifiers.
Gevoeligheid	90 dB/2.83 volts/meter
Luidsprekerbezetting	Custom air core coil and low DCR steel laminate inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Overall system thermal/current protection.
Ingangen	Push style with banana jacks
Aanbevolen versterkervermogen	20-150 W per kanaal
Horizontale afstraling	80°
Verticale afstraling	80°

Technische specificaties

Scheidingsfrequentie	2,900 Hz
Hogetonenunit	1" × 1.4" (2.6cm × 3.6cm) Folded Motion Transducer with 5.25" × 1.75" (13.3cm × 4.4cm) diaphragm
Lagetonenunit	4" (10.2cm) paper cone with stamped steel basket. Non-resonant asymmetrical chamber format. Rigid structured dust cap to reduce cone break-up modes. Folded bass reflex port.
Afmetingen	12.6" x 5.6" x 5.7 " (32cm x 14.3cm x 14.5cm)
Gewicht	6 lbs. (2.72 kg)