

MartinLogan Motion F20

Vloerstaande luidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion F20
Productcategorie	Vloerstaande luidsprekers
Frequentiebereik	35 Hz - 25kHz $\pm$ 3 dB
Impedantie	4 Ω
Gevoeligheid	92 dB
Afmetingen (H x W x D, with feet)	44-3/4" x 11-3/4" x 14-1/4" 112.7cm x 29.8cm x 36.2cm
Afstraling tweeter (horizontaal x verticaal)	90° x 90°
Aanbevolen versterkervermogen	20 - 300 W
Scheidingsfrequentie	230 Hz, 2,600 Hz (3-way)

Technische specificaties

Hogetonenunit	1" x 1.4" (2.6 x 3.6cm) Gen2 Obsidian Folded Motion Tweeter with 9.2 in2 (59.4 cm2) diaphragm
Middentonenunits	5.5" (14cm) Woven Fiberglass cone with cast polymer basket. Non- resonant sealed chamber format. Unibody cone construction.
Lagetonenunit	2x 6.5" (16.5cm) aluminum cones with cast polymer baskets. Non-resonant asymmetrical chamber format. Unibody cone construction.
Behuizing	Bottom Ported
Luidsprekerterminals	Custom bi-amp/bi-wire capable 5-way binding posts
Gewicht	60lbs / 27.2kg
Afwerking	Gloss Zwart, Walnoot, en Satin Wit