

MartinLogan Motion XT F100

Vloerstaande luidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion XT F100
Productcategorie	Vloerstaande luidsprekers
Frequentiebereik	31 Hz - 25 kHz $\pm$ 3 dB
Impedantie	4 Ω
Gevoeligheid	92 dB
Afmetingen (H x W x D, with feet)	47-3/4" x 12-1/2" x 15" 121.3cm x 31.75cm x 34.3cm
Afstraling tweeter (horizontaal x verticaal)	90° x 45°
Aanbevolen versterkervermogen	20 - 450 W
Scheidingsfrequentie	280 Hz, 2600 Hz (3-way)

Technische specificaties

Hogetonenunit	1.25" x 2.4" (3.2 x 6.1cm) Gen2 Obsidian Folded Motion XT Tweeter with 12.4 in ² (79.8 cm ²) diaphragm
Middentonenunits	6.5" (16.5cm) Nomex Reinforced Kevlar® cone with cast aluminum basket. Non-resonant sealed chamber format. Unibody cone construction.
Lagetonenunit	3x 6.5" (16.5cm) aluminum cones with cast aluminum baskets. Non-resonant asymmetrical chamber format. Unibody cone construction.
Behuizing	Bottom Ported
Luidsprekerterminals	Custom bi-amp/bi-wire capable 5-way binding posts
Gewicht	76lbs / 34.5kg
Afwerking	Gloss Zwart, Walnoot, en Satin Wit