

MartinLogan Motion XTW6-LCR

Inbouwluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Motion XTW6-LCR
Productcategorie	Inbouwluidsprekers
Frequentiebereik	44 - 25,000 Hz $\pm$ 3dB
Impedantie	4 Ω . Compatible with 8 Ω
Gevoeligheid	93dB @2.83V/ 1 meter
Luidsprekerbezetting	Custom air core coil inductors, polyester film capacitors in series and low DF electrolytic capacitors FMT thermal/current protection.
Afstraling tweeter (horizontaal x verticaal)	80 x 30 degrees
Aanbevolen versterkervermogen	Range 50-300 Ws
Scheidingsfrequentie	260, 2470 Hz

Technische specificaties

Hogetonenunit	FMT Transducer 1.27" x 2.4" (3.22cm x 6.09cm) Opening 4.5" x 2.75" (11.43cm x 6.98cm) Diaphragm
Type wisselfilter	3 way
Connector	Push style
Maximale belastbaarheid	150 Ws
Middentonenunit	One 6.5" (16.51 cm) cast aluminum basket, black Kevlar with Nomex backer cone, Sealed back chamber format. Concave dust cap
Afmetingen (overall size)	28" x 7.69" x 3.67" (71.12 x 19.5 x 9.31cm)
Benodigde wandopening inclusief tolerantie	6.64" x 27" (16.9 x 68.5cm)
Uitsteek vanaf wand	0.13" (0.32cm)
Diepte achter wand	3.54" (8.99cm)
Gewicht	18.9 lbs. each (8.6 kg)