

MartinLogan Sistine 4XC

Inbouwluidsprekers



Technische specificaties

Merk	MartinLogan
Model	Sistine 4XC
Productcategorie	Inbouwluidsprekers
Frequentiebereik	63-25,000 Hz $\pm$ 3 dB
Impedantie	4 Ω . Compatible with 4, 6, or 8 ohm rated amps.
Gevoeligheid	92 dB @ 2.83 volts/ meter
Luidsprekerbezetting	Custom air core coil inductors, polypropylene film capacitors, en low DF electrolytic capacitors. Thermal/current protection.
Afstraling tweeter (horizontaal x verticaal)	30° x 80°
Scheidingsfrequentie	400, 2250 Hz
Hogetonenunit	1.25 x 2.4 inch (3.2 x 6.1 cm) Folded Motion XT Obsidian transducer with 4.5 x 2.75 inch (11.4 x 7 cm) diaphragm.

Technische specificaties

Middentonenunits	Twee 3.5-inch (8.9 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Lagetonenunit	8-inch (20.3 cm) black unidirectional carbon fiber multi-section cone with Nomex® backer and cast aluminum basket, sealed back chamber format. Concave dust cap.
Aanbevolen versterkervermogen	20-300 W
Maximale belastbaarheid	150 W
Luidsprekerterminals	Push style
Afmetingen (overall size)	12.8 x 7.5 inch (325 x 190 mm)
Benodigde wandopening inclusief tolerantie	11.46 inch (291 mm)
Uitsteek vanaf wand	0.26 inch (6.6 mm)
Diepte achter wand	7.2 inch (184 mm)
Gewicht	13.5 lb (6.1 kg)