

Naim Audio NSC 222

Streamers & muziekserver



Technische specificaties

Merk	Naim Audio
Model	NSC 222
Productcategorie	Streamers & muziekserver
Analoge ingangen	1 x moving magnet phono 1 x 8-pin DIN (compatible with 5-pin DIN cables) 1 x RCA stereo pair Line level inputs (RCA/DIN): Impedance 47k, 2.2V typical, 7.5Vrms Max Compatible with 5 pin DIN MM phono: 47k/470pF, 5mV, 23dB overload (75mV max)
Digitale ingangen	2 x Optical TOSLINK (tot 24bit/96kHz) 1 x coaxial RCA (tot 24bit/192kHz, DoP 64Fs) 1 x coaxial BNC (tot 24bit 192kHz, DoP 64Fs)
Analoge uitgangen	1 x XLR pair (7Vrms max) 1 x RCA pair (7Vrms max) 1 x 6.35mm headphone jack (Headphone 1.5W into 16Ω)
Netwerk	Ethernet (10/100Mbps), Wi-Fi (802.11a/b/g/n/ac), BLE v4.2
Bediening	5.5" colour display and four buttons for quick access to standby, play/pause, inputs and favourites. Volume control.

Technische specificaties

Audioformaten	WAV - tot 32bit/384kHz FLAC and AIFF - tot 24bit/384Hz ALAC (Apple Lossless) - tot 24bit/384Hz MP3 - tot 48kHz, 320kbit (16 bit) AAC - tot 48kHz, 320kbit (16 bit) OGG and WMA - tot 48kHz (16 bit) DSD - 64 and 128Fs M4A - tot 48kHz, 320kbit (16 bit) Gapless playback supported on all formats
Frequentiebereik, digitaal	Digital: 3Hz to 27kHz -3dB
Frequentiebereik - line	Line : 3 Hz to 40 kHz -3 dB
Vervorming - Line	Line: 0.0025% @2.2V input volume at 0dB, 1kHz (Line: 0.015% @2.2V input volume at 0dB, 20kHz)
Analoge versterkingsfactor	Pre-amplifier at max volume 15.5dB Phono stage MM 40dB
Hoofdtelefoonuitgangen	1 x jack 6,35 mm
Overige uitgangen	Optical 3.5 mm output for synchronized control of compatible product (eg. NAP 250/350)
USB-poorten	2x USB Type A socket (front and rear - 1.6A charge)
Frequentiebereik - Phono	MM: -3dB at 10Hz, RIAA +/-0.1dB
Vervorming - Phono	MM: < noise floor
Wifi	Wi-Fi (802.11 b/g/n/ac) met internal antenna, integrated into the heat sink (patent GB2524815B)
Multiroom	Multiroom streaming and its "Party Mode" (sync tot six Naim streamers), en control them via the "Focal & Naim" application
Streaming in stereo	Apple AirPlay 2, Bluetooth, Chromecast, Internet Radio, Qobuz, Roon Ready, Spotify®Connect, TIDAL, UPnP™
Bediening via app	Focal & Naim App
Bedieningssysteem	Zigbee® RF4CE
Ondersteunde mobiele systemen	Android, iOS
Automatische stand-by	<20 min.
Stroomverbruik, uitgeschakeld	< 0.3W
Stroomverbruik in stand-by	< 0.5W

Technische specificaties

Stroomverbruik in netwerkstand-by	< 2W
Stroomverbruik bij gebruik	25 W
Netvoeding	115V or 230V, 50/60Hz
Optionele voedingen	NPX 300
Breedte	43.2 cm / 8.14 in
Hoogte	9.15 cm / 3.62 in
Diepte	31.75 cm / 12.5 in
Gewicht	11 kg / 24.25 lb