

Paradigm Loudspeakers CI Elite E3 LCR v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Elite E3 LCR v2
Productcategorie	Inbouwluidsprekers
Ontwerp	3-driver, dual passive radiators, 2-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System, Machined Aluminum Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	3rd-order electro-acoustic at 2.3 kHz
Frequentierespons op de as	±3 dB from 93 Hz - 22 kHz
Frequentierespons 30° buiten de as	±3 dB from 93 Hz - 19 kHz
Hogetonenunit	1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Passieve radiatoren	Twee 5.5" (13.9cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Midden-/lagetonenunit	Twee 5.5" (13.9cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, 1.5" high-temp voicecoil, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	92 dB / 89 dB
Onderste grensfrequentie	57 Hz
Aanbevolen versterkervermogen	15-200 W
Maximaal ingangsvermogen	130 W
Afmetingen inbouwopening	31"x 6-5/8" (78.8cm x 16.9cm)
Minimale inbouwdiepte achter ½-inch wandplaat	3-7/8" (9.8cm)
Afmetingen (H x B x D) (INCLUDES GRILLE).	32" x 7-5/8" x 4-1/8" (81.4cm x 19.5cm x 10.5cm)
Gewicht	23.0 lbs (10.4 kg)
Afwerkingen	Wit, paintable grille, black speaker