

Paradigm Loudspeakers CI Elite E5 LCR v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Elite E5 LCR v2
Productcategorie	Inbouwluidsprekers
Ontwerp	4-driver, dual passive radiators, 3-way, shallow enclosure in-wall design, Advanced SHOCK-MOUNT™ System, Machined Aluminum Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	3rd-order electro-acoustic at 3 kHz 2nd-order electro-acoustic @ 450 Hz
Frequentierespons op de as	± 3 dB from 82 Hz - 22 kHz
Frequentierespons 30° buiten de as	± 3 dB from 82 Hz - 19 kHz

Technische specificaties

Hogetonenunit	Coaxial 1" (2.5cm) Aluminum Magnesium Ceramic AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) en Perforated Phase-Aligning (PPA™) Tweeter Lens, Patented Dual-Sync™ Continuous Flux Motor
Middentonenunit	Coaxial 6" (15.2cm) AL-MAG™ Cone with SHOCK-MOUNT™ Isolation Mounting System, a 2" high-temp multi-layered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor
Lagetonenunit	Twee 6.5" (16.5cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, 1.5" high-temp voicecoil, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Passieve radiatoren	Twee 6.5" (16.5cm) Aluminum Magnesium (AL-MAG™) Cones with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast-Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	94 dB / 91 dB
Onderste grensfrequentie	56 Hz
Aanbevolen versterkervermogen	15-220 W
Maximaal ingangsvermogen	150 W
Afmetingen inbouwopening	42" x 8-1/2" (106.6cm x 21.5cm)
Minimale inbouwdiepte achter 1/2-inch wandplaat	3-7/8" (9.8cm)
Afmetingen (H x B x D) (INCLUDES GRILLE).	43" x 9-1/2" x 4-1/8" (109.2cm x 19.5cm x 10.5cm)
Gewicht	34.0 lbs (15.4 kg)
Afwerkingen	Wit, paintable grille, black speaker