

Paradigm Loudspeakers CI Pro P80-SM v2

Inbouwluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	CI Pro P80-SM v2
Productcategorie	Inbouwluidsprekers
Ontwerp	3-driver, 2-way in-ceiling, Advanced SHOCK-MOUNT™ System, Nylon Reinforced Baffle
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd-order electro- acoustic at 2.5 kHz
Frequentierespons op de as	± 3 dB from 64 Hz - 22 kHz
Frequentierespons 30° buiten de as	± 3 dB from 64 Hz - 18 kHz
Hogetonenuit	Twee 1" (2.5cm) Aluminum Magnesium Ceramic (AL-MAC™) Tweeter with Exclusive Perforated Phase-Aligning (PPA™) Tweeter Lens and Reduced Edge Diffraction (RED™) Technology

Technische specificaties

Midden-/lagetonenunit	8" (20.3cm) CARBON-X™ Cone with overmolded Active Ridge Technology (ART™) surround, Advanced Shock-Mount™ System, FEA-Optimized Ultra Rigid Cast- Aluminium Baskets
Gevoeligheid (ruimte / anechoïsch)	92.5 dB / 88.5 dB
Onderste grensfrequentie	40 Hz
Aanbevolen versterkervermogen	15-110 W Mono; 15-55 W / channel Stereo Input
Maximaal ingangsvermogen	100 W Mono / 50 W Stereo
Afmetingen inbouwopening	9-3/16" (23.4cm) dia.
Minimale inbouwdiepte achter 1/2-inch wandplaat	3-7/8" (9.8cm)
Afmetingen (H x B x D) (INCLUDES GRILLE).	10-1/4" (diameter) x 4-1/2" (depth) (26.1cm x 11.4cm)
Gewicht	7.0 lbs (3.2 kg)
Afwerkingen	Wit, paintable grille, black speaker