

Paradigm Loudspeakers Premier 520LCR v2

Centerluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	Premier 520LCR v2
Productcategorie	Centerluidsprekers
Ontwerp	4-driver, 3-way sealed LCR speaker with AL-MAC, AL-MAG, Carbon-X, OSW™, en PPA™
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd Order Electro-acoustic at 1.5kHz (tweeter/midrange) 2nd Order Electro-acoustic at 650Hz (midrange/woofer)
Frequentierespons op de as	±3dB from 75Hz - 23kHz
Frequentierespons 30° buiten de as	±3dB from 75Hz - 20kHz
Hogetonenunit	1" (25mm) AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) en Perforated Phase-Aligning (PPA™) Tweeter Lens, ferro-fluid damped / cooled

Technische specificaties

Middentonenunit	Coaxial 6" (152mm) AL-MAG™ Cone, a 2" high-temp multilayered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor
Lagetonenunit	Twee 6" (152mm) Ultra-High Excursion CARBON-X™ Unibody Cone, Gen3 Active Ridge Technology (ART™) met Vertical Mounting System, en a 1" hightemp multi-layered voice coil with ventilated Apical™ former
Gevoeligheid (ruimte / anechoïsch)	93dB / 90dB
Onderste grensfrequentie	50Hz (DIN)
Aanbevolen versterkervermogen	15-120 Ws
Maximaal ingangsvermogen	80 Ws
Afmetingen (H x B x D) (INCLUDES GRILLE).	8.3" x 23.4" x 12" (21.1 cm x 59.4 cm x 30.5 cm)
Gewicht	31.1 lbs (14.1 kg) each
Afwerkingen	Piano Zwart, Zwart Walnoot, Walnoot, Satin Wit