

Paradigm Loudspeakers Premier 620C v2

Centerluidsprekers



Technische specificaties

Merk	Paradigm Loudspeakers
Model	Premier 620C v2
Productcategorie	Centerluidsprekers
Ontwerp	4-driver, 2-passive radiator, 3-way sealed center channel speaker with AL-MAC, AL-MAG, Carbon-X, OSW™, en PPA™
Impedantie	Compatible with 8 Ω
Wisselfilter	2nd Order Electro-acoustic at 1.7kHz (tweeter/midrange) 2nd Order Electro-acoustic at 750Hz (midrange/woofer)
Frequentierespons op de as	±3dB from 49Hz - 23kHz
Frequentierespons 30° buiten de as	±3dB from 49Hz - 20kHz
Hogetonenunit	1" (25mm) AL-MAC™ Ceramic Dome with Oblate Spheroid Waveguide (OSW™) en Perforated Phase-Aligning (PPA™) Tweeter Lens, ferro-fluid damped / cooled

Technische specificaties

Middentonenunit	Coaxial 6" (152mm) AL-MAG™ Cone, a 2" high-temp multi-layered voice coil with Apical™ former, Patented Dual-Sync™ Continuous Flux Motor
Lagetonenunit	Twee 7" (177mm) Ultra-High Excursion CARBON-X™ Unibody Cone, Gen3 Active Ridge Technology (ART™) met Vertical Mounting System, en a 1" hightemp multi-layered voice coil with ventilated Apical™ former
Passieve radiatoren	Twee 7" (177mm) Ultra-High Excursion CARBON-X™ Unibody Passive Raditators with Gen3 Active Ridge Technology (ART™) en Vertical Mounting System
Gevoeligheid (ruimte / anechoïsch)	93dB / 90dB
Onderste grensfrequentie	33Hz (DIN)
Aanbevolen versterkervermogen	15 - 180 Ws
Maximaal ingangsvermogen	120 Ws
Afmetingen (H x B x D) (INCLUDES GRILLE).	8.9" x 41" x 13.7" (22.6 cm x 104.1 cm x 34.8 cm)
Gewicht	48.1 lbs (21.8 kg) each
Afwerkingen	Piano Zwart, Zwart Walnoot, Walnoot