

REL Acoustics T/9x SE

Subwoofers



Technische specificaties

Merk	REL Acoustics
Model	T/9x SE
Productcategorie	Subwoofers
Type	Front-firing active driver, down-firing passive radiator
Versterkertype	Klasse A/B
Uitgangsvermogen	300 W (RMS)
Actieve driver: formaat en materiaal	10 in. (250mm) long-throw, FibreCarbon™ cone, inverted Carbon Fibre centre cap, steel chassis
Passieve radiator: formaat en materiaal	10 in. (250mm) long-throw, FibreAlloy™ cone, inverted alloy centre cap, steel chassis
Onderste grensfrequentie	-6 dB at 27Hz Low Frequency
Ingangsaansluitingen	High Level Neutrik Speakon, (1) Lijnniveau RCA,(1) LFE RCA
Uitgangsaansluitingen	N/A

Technische specificaties

Draadloze verbinding	REL Arrow system [required]. Sold separately
Dubbel parametrisch filter	Nee
Elektronische beveiliging	Ja
DC-beveiliging	Ja
Kortsluitbeveiliging uitgang	Ja
Netspanning	220-240 volts, 110-120 volts for certain markets
Zekeringen	3.15 Amp semi delay 220 volts operation. 7 Amp semi delay 120 volts operation
Netsnoer	Ja
Neutrik speakON	10 Meters (33'6") Nominal
Afwerking	Italian Racing Red Lacquer, 7 coats